



SAFE

FIRE HOSE REEL

Design Features :

- Manufactured as per BS EN671-1 Standard.
- Hose Reel discs are manufactured using 1.2mm Electro galvanised steel sheets and has ribs that gave extra strength, which in turn avoid twisting.
- Hose reel drum painted with red powder coating or chrome in stainless steel finish are available upon request
- Plastic nozzle supplied has jet/spray/shut-off operations.
- Chrome plated brass nozzle is available upon request.
- Hose has working pressure of 15 Bar and bursting pressure of 50 Bar and it is red in color, Black color also available upon request.
- Inlet stop valve 1" size in made of brass and finished with chrome. Brass finish available upon request.
- Each unit is hydrostatically tested at 18 Bar.
- For Fixed Hose Reel, a hose guide could be supplied upon request.
- Swinging Hose Reel is mounted on an arm which swings 180° and the hose can be run out in all directions without a hose guide.
- In automatic models, the valve opens automatically within three revolutions of the reel.
- Fire Hose Reel is an efficient and reliable fire-fighting unit suitable for use in all types of buildings.
- The water is supplied through the center of the reel, so the unit is always ready for immediate use.

Optional :

Kite mark, LPCB and CE approved fire hose reel available upon request.



SPECIFICATIONS

Type	Model No	Size of Hose	Reel Dia A (mm)	Depth B (mm)	Version
Fixed Manual	NFH-F-25M	25mm dia(1")Length=30M	550	285	
	NFH-F-19M	19mm dia(¾")Length=30M	550	240	
Fixed Automatic	NFH-F-25A	25mm dia(1")Length=30M	550	285	
	NFH-F-19A	19mm dia(¾")Length=30M	550	240	
Swinging Manual	NFH-C-25M	25mm dia(1")Length=30M	550	260	Arm Type
	NFH-C-19M	19mm dia(¾")Length=30M	550	210	Arm Type
	NFH-W-25M	25mm dia(1")Length=30M	550	275	Pipe Type
	NFH-W-19M	19mm dia(¾")Length=30M	550	230	Pipe Type
Swinging Automatic	NFH-C-25A	25mm dia(1")Length=30M	550	275	Arm Type
	NFH-C-19A	19mm dia(¾")Length=30M	550	230	Arm Type
	NFH-W-25A	25mm dia(1")Length=30M	550	275	Pipe Type
	NFH-W-19A	19mm dia(¾")Length=30M	550	230	Pipe Type



NAFFCO

FIRE HOSE RACK CABINET

Design Features :

- Cabinet with door made of 1.2mm electro-galvanised steel sheet.
- Recessed type door lock & handle with chrome plating.
- Cabinet painted with red electrostatic powder coating. Other colours are available on request.
- Superior quality PU Lined 1.5" or 2.5" fire hose.
- Hose Rack mounted inside the cabinet.
- 1.5" or 2.5" Angle valve.
- 1.5" or 2.5" brass finish adjustable fog nozzle.

Optional :

- 1.5" or 2.5" Angle valve with built-in pressure reduction capacity.
- Stainless steel cabinet with brush or mirror finish available upon Request.



NAFFCO NF/750

SPECIFICATIONS

Model No	Size of Hose	Dimensions cm	Material of Construction	Cabinet Mounting
NF/750S	2.5" dia Length=100ft 1.5" dia Length=100ft	H=85 W=80 D=25 H=75 W=70 D=20	Electro-galvanised Steel Sheet	Surface Mounted
NF/SB750S	2.5" dia Length=100ft 1.5" dia Length=100ft	H=85 W=80 D=25 H=75 W=70 D=20	Stainless Steel Brush Finish	Surface Mounted
NF/SM750S	2.5" dia Length=100ft 1.5" dia Length=100ft	H=85 W=80 D=25 H=75 W=70 D=20	Stainless Steel Mirror Finish	Surface Mounted
NF/750R	2.5" dia Length=100ft 1.5" dia Length=100ft	H=85 W=80 D=25 H=75 W=70 D=20	Electro-galvanised Steel Sheet	Recessed
NF/SB750R	2.5" dia Length=100ft 1.5" dia Length=100ft	H=85 W=80 D=25 H=75 W=70 D=20	Stainless Steel Brush Finish	Recessed
NF/750R	2.5" dia Length=100ft 1.5" dia Length=100ft	H=85 W=80 D=25 H=75 W=70 D=20	Electro-galvanised Steel Sheet	Recessed

Note : For recessed cabinet, the wall opening should be 1cm additional on all sides.

FIRE HOSE CABINET

Design Features :

- Cabinet with door made of 1.2mm electro-galvanized steel sheet.
- Recessed type door lock & handle with chrome plating.
- Cabinet painted with red electrostatic powder coating. Other colours are available on request.
- 2.5"x100 feet polyester fire hose. Other sizes and lengths are available on request.
- 2/2.5" landing valve with quick coupling. Other models also available.
- 2.5" water branchpipe.

Optional :

- 10 Lbs Dry Powder or Clean Agent Fire Extinguisher.



NAFFCO NF/450

SPECIFICATIONS

Model No	Size of Hose	Dimensions cm	Material of Construction	Cabinet Mounting
NF/450S	2.5" dia Length=100ft	H=70 W=75 D=28	Electro-galvanised Steel Sheet	Surface Mounted
NF/SB450S	2.5" dia Length=100ft	H=80 W=75 D=31	Stainless Steel Brush Finish	Surface Mounted
NF/SM450S	2.5" dia Length=100ft	H=80 W=75 D=31	Stainless Steel Mirror Finish	Surface Mounted
NF/450R	2.5" dia Length=100ft	H=70 W=70 D=28	Electro-galvanised Steel Sheet	Recessed
NF/SB450R	2.5" dia Length=100ft	H=70 W=70 D=28	Stainless Steel Brush Finish	Recessed
NF/SM450R	2.5" dia Length=100ft	H=70 W=70 D=28	Stainless Steel Mirror Finish	Recessed

Note : For recessed cabinet, the wall opening should be of 1cm additional on all sides.



FIRE HOSE REEL DOUBLE CABINET

Design Features :

- Cabinet with door made of 1.2mm electro-galvanised steel sheet.
- Recessed type door lock & handle with chrome plating.
- Cabinet painted with red electrostatic powder coating. Other colours are available on request.
- Upper compartment consists of: Hose reel with 1" x 30M hose or 3/4" x 30M hose.
- Lower compartment consists of: 2.5" x 100 feet polyester fire hose. Other sizes and lengths available on request.
- 2/2.5" landing valve with quick coupling. Other models also available & 2.5" water branch pipe

Optional :

- 10Lbs Dry powder or Clean Agent Fire Extinguisher.
- LPCB approved fire hose reel double cabinet available upon request.



NAFFCO NF/900

SPECIFICATIONS

Model No	Size of Hose	Dimensions cm	Material of Construction	Valve Opening	Cabinet Mounting
NF/900S	25mm dia(1") Length=30M	H=149 W=72D=28	Electro-galvanised Steel Sheet	Manual	Surface Mounted
NF/900AS	25mm dia(1") Length=30M	H=149 W=72D=28	Electro-galvanised Steel Sheet	Automatic	Surface Mounted
NF/SB900AS	25mm dia(1") Length=30M	H=155 W=72 D=31	Stainless Steel Brush Finish	Automatic	Surface Mounted
NF/SM900S	25mm dia(1") Length=30M	H=155 W=72D=31	Stainless Steel Mirror Finish	Manual	Surface Mounted
NF/900R	25mm dia(1") Length=30M	H=140/150 W=70 D=28	Electro-galvanised Steel Sheet	Manual	Recessed
NF/900AR	25mm dia(1") Length=30M	H=140/150 W=70 D=28	Electro-galvanised Steel Sheet	Automatic	Recessed
NF/SB900R	25mm dia(1") Length=30M	H=140/150 W=70 D=28	Stainless Steel Brush Finish	Manual	Recessed
NF/SM900AR	25mm dia(1") Length=30M	H=140/150 W=70 D=28	Stainless Steel Mirror Finish	Automatic	Recessed

Note : For recessed cabinet, the wall opening should be 1cm additional on all sides.

CUSTOM BUILT CABINETS

Apart from the Standard range of cabinets, NAFFCO can also fabricate cabinets according to client's specific requirements. This includes cabinets with marble clad or wooden laminate doors with cabinet colors to match the surrounding decor. Special door locking devices can also be included for the fabrication. Our state of the art fully automated production facility including CNC machine center enable us to meet the modern commercial, residential and institutional requirements.



Special Fire Hose Reel Cabinet



Wooden laminated Door