

Mobile Foam (AFFF) Extinguishers

Features:

- Ready for instant use and simple to operate.
- Fully controlled and easy operation by rust free brass valve.
- Cart and cylinder are made of rugged steel and welded to meet extreme use conditions.
- Easily transportable.
- Highly visible pressure-indicating gauge.
- Electrostatic powder painting after shot blasting ensures maximum corrosion resistance.
- Internally coated with Polyolefin & thermosetting polymer powder using resin for corrosion resistance.

Options:

- For three wheels, suffix "S"
- Other hose lengths available upon request
- Special Extinguishers which are freeze protected up to -20°C



Stored Pressure

Model	NTF25	NTF10G	NTF50	NTF100	NTF35G
Extinguisher Capacity	25Litres	10Gallons	50Litres	100Litres	35Gallons
Fire Rating	13A IB	13A IB	13A IIB	13A IIIB	13A IVB
Working Pressure	15Bar				
Test Pressure	30Bar				
Total Weight	58Kg	70Kg	95Kg	170Kg	227Kg
Range of Discharge	7-8m	7-8m	7-8m	7-8m	7-8m
Duration of Discharge	25-30Sec	30-33Sec	45-50Sec	90-95Sec	110-115Sec
Operating Temperature	+ 5°C to + 60°C				
Hose Length	3m	3m	5m	7m	7m

External CO₂ Cartridge

Model	NTFC25	NTFC10G	NTFC50	NTFC100	NTFC35G
Extinguisher Capacity	25Litres	10Gallons	50Litres	100Litres	35Gallons
Fire Rating	13A IB	13A IB	13A IIB	13A IIIB	13A IVB
Working Pressure	15Bar				
Test Pressure	30Bar				
Total Weight	65Kg	82Kg	102Kg	189Kg	236Kg
Range of Discharge	7-8m	7-8m	7-8m	7-8m	7-8m
Duration of Discharge	25-30Sec	30-33Sec	45-50Sec	90-95Sec	110-115Sec
Operating Temperature	+ 5°C to + 60°C				
Hose Length	3m	3m	5m	7m	7m



Foam Master

Features:

- Ideal for rapid deployment to flammable liquid fires & chemical spills.
- Can be operated by one person.
- Foam tank made of stainless steel.
- Externally powder painted (yellow color)

Model	NFM 150L	NFM 500L
Capacity*	150Litres	500Litres
Foam Inductor	2" dia, 1-6% variable	
Foam Branchpipe	2 inch	
Fire Hose	1 1/2" x 15m	2 1/2" x 15m

* Other capacity available upon the request

